

DECLARATION OF PERFORMANCE

No. <u>BETUN 70/100</u>

1. Name and identity code:

Bitumen for paving CEPSASFALT 70/100 BETUN 70/100

(E

2. Name and address of manufacturer:

CEPSA COMERCIAL PETRÓLEO, S.A Pº de la Castellana, nº 259 A – Torre CEPSA 28046 Madrid (Spain)

Tel.: 91 337 60 00 www.cepsa.es

3. Applications:

Construction and maintenance of roads, aerodromes and other paved areas (sealed against penetration)

4. System of assessment and verification of performance compliance: 2+

5. Notified body:

AENOR 0099

• Task performed: Factory control assessment

• Certificates: 0099/CPR/B11/0199 – Date issued: 30/07/2010

0099/CPR/B11/0203 - Date issued: 30/07/2010 0099/CPR/B11/0206 - Date issued: 30/07/2010 0099/CPR/B11/0208 - Date issued: 30/07/2010 0099/CPR/B11/0209 - Date issued: 30/07/2010

6. Declared performance:

or becared performances		
	Б. С	Harmonised
Essential characteristics	Performance	technical
		specifications
Consistency at intermediate service temperatures		EN 12591:2009
Penetration at 25° C	70-100 x 0.1 mm	
Consistency at high service temperatures		
Softening point	43-51° C	
Resistance to hardening at 163°C (EN-12607-1)		
Durability of the consistency at intermediate service		
temperatures, with the test method used		
Retention to penetration at 25°C	≥ 46%	
Durability of the consistency at high service temperatures, with		EN 12591,2009
the test method used		
Increased softening point	≤11º C	
Penetration rate	-1.5 to+ 0.7	
Consistent temperature dependence		
Dynamic viscosity at 60° C	PND	
Fragility at low service temperatures		
Fraass breaking point	≤ -10° C	



- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

Gerardo Pardo Alvarez-Buylla Director of the Asphalt Unit CEPSA COMERCIAL PETRÓLEO, S.A. Madrid, 30 april 2021