

DECLARATION OF PERFORMANCE

No. **PMB 45/80-60**

1. Name and identity code:

Bitumen for paving ELASTER BM-3b PMB 45/80-60

2. Name and address of manufacturer:

CEPSA COMERCIAL PETROLEO, S.A. P^o de la Castellana, n^o 259 A – Torre CEPSA 28046 Madrid (Spain) Tel.: 91 337 60 00 www.cepsa.es

3. Applications:

Construction and maintenance of roads, aerodromes and other paved areas (sealed against penetration)

4. System of assessment and verification of performance compliance: 2+

5. Notified body:

- AENOR 0099
- Task performed: Factory control assessment
- Certificates: 0099/CPR/B11/0203 Date issued: 30/07/2010 0099/CPR/B11/0208 – Date issued: 30/07/2010

6. Declared performance:

		Harmonised
Essential characteristics	Performance	technical
		specifications
Consistency at intermediate service temperatures		
Penetration at 25° C	Class 4	
Consistency at high service temperatures		
Softening point	Class 6	
Cohesion		
Strength-Ductility (traction at 50 mm/min)	Class 3	
Durability. Resistance to hardening (EN 12607-1)		EN 14023:2010
Retained penetration	Class 7	EN 14023:2010
Increased softening point	Class 3	
Change of mass	Class 5	
Fragility at low service temperatures		
FRAASS fragility point (EN 12593)	Class 6	
Elastic recovery		
Elastic recovery at 25°C	Class 5	1





- The performance of the product declared in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued at the sole responsibility of the manufacturer identified in point 2.
- Signed by and on behalf of the manufacturer by:

Gerardo Pardo Alvarez-Buylla Director of the Asphalt Unit CEPSA COMERCIAL PETRÓLEO, S.A.

Madrid, 30 april 2021